



Reprezentanta oficiala: "Kioti-Romania & Rep. Moldova" din Craiova, jud. Dolj, RO; www.kiotiromania.ro



NEW Series **KIOTI DK4510N/HS & DK5010N/HS & DK5510N/HS** w CABINE



Model Nou, 2016 tractor KIOTI :	4x4	<u>DK4510N/HS</u>	<u>DK5010N/HS</u>	<u>DK5510N/HS</u>
Motor Euro3(45&50CP);Euro4/55CP		Euro 3 / Stage IIIA	Euro 3 / Stage IIIA	Euro4 / Stage IIIB
Producator: Coreea de Sud / Korea	Kr.	Daedong - Korea	Daedong - Korea	Daedong - Korea
Model motor Dadong/made Korea		4B243LWL-E1	4B243LWL-E	3FT-TL4-E
Puterea nominala: (C.P. / KW)	C.P.	45C.P. / 33,6kW	49,3C.P. / 36kW	55C.P. / 41kW
Nr. de cilindri motor		4	4	3
Cilindreea / Turatia nominala	cm3	2435 / 2600rot/min	2435 / 2600	1826 TURBO
Alezaj & Cursa	mm	87x102,4	87x102,4	87x102,4
Raport de compresie		22:1	22:1	17,4:1
Ordinea de injectie		1-3-4-2	1-3-4-2	1-2-3
Greutate motor	kg	220	220	240
Capacitate rezervor motorina	litri	45	45	45
Priza de putere spate:independenta	rpm	540/540E	540/540E	540/540E
Control ridicar hidraulic in 3 pt.		Pozitie, Forta, Mixt	Pozitie, Forta, Mixt	Pozitie, Forta, Mixt
TOTAL Debit Pompa Hidraulica:	l/min	55,1	55,1	55,1
Pompa hidrulica principala	l/min	36,4	36,4	36,4
Pompa hidraulica pt. servodirectie	l/min	18,7	18,7	18,7
Cat. ridicar hidraulic in 3 puncte		Cat. 1	Cat. 1	Cat. 2
Capacitate ridicare in rotula tirant	Kg.f	1360	1360	1360
Cap. ridicare la 24"/61cm de rotule	Kg.f	1230	1230	1230
Capacitate de remorcare	Kg.f	4300	4300	4300
Nr. Std. de prize hidraulice spate		4	4	4
Transmisia – Mecanica sincronizata		Manuala/H-Shuttle	Manuala/H-Shuttle	Manuala/H-Shuttle
Cutia de viteze : nr. de trepte	F/S	16 / 16	16 / 16	16 / 16
Servodirectia: asistata hidraulic		Power Steering	Power Steering	Power Steering
Franele:		discuri umede	discuri umede	discuri umede
Ambreiajul:		uscat, monodisc	uscat, monodisc	uscat, monodisc
Diferential blocabil roti spate		Spate Std.	Spate Std.	Spate Std.
Anvelope : Agricole diagonale Std.	F/S	8-16"/ 12.4-24"	8 -16"/ 12.4-24"	8-16"/ 12.4-24"
: Turf / Iarba radiale	F/S	31-13.5-15"/21.5L-16.1	31-13.5-15"/21.5L-16.1	31-13.5-15"/21.5L-16.1
: Industriale radiale	F/S	12-16.5" / 14.9-24"	12-16.5" / 14.9-24"	12-16.5" / 14.9-24"
Dimensiuni exterioare tractor :		45CP/Euro 3	50CP/Euro3	55CP Turbo/Euro4
* Lungime tractor cu rid. hidraulic	mm	3157/3580	3157/3580	3157
* Latime tractor - STD Reglabil	mm	1500-1596	1500-1596	1500-1596
- Ingust ("N"pt. VIE)	mm	1410	1410	1410
- Ecartament roti fata - Reglabil	mm	1254-1284	1254-1284	1254-1284
- Ingust/Narrow-VIE	mm	1164	1164	1164
- Ecartament roti spate - Reglabil	mm	1185-1251	1185-1251	1185-1251
- Ingust/Narrow-VIE	mm	1141	1141	1141
* Inaltime tractor cu ROPS - STD	mm	2432	2432	2432
- Ingust/Narrow-VIE	mm	2232	2232	2232
* Inaltime tractor cu CABINA	mm	2165	2165	2165
*Ampatament tractor seria "DK10"	mm	1810	1810	1810
* Garda la sol	mm	388	388	388
* Raza de intoarcere/bracaj	mm	2650	2650	2650
Greutatea tractorului cu cadru ROPS	kg	1570	1570	1581
Greutatea tractorului cu CABINA	kg	1850	1850	1850

Reprezentanta oficiala "KIOTI-ROMANIA": Acecop Trade Consult SRL,Craiova - **Mobil: 0720-700.501.**